### SUMMER COURSE 2021 GREEN INFRASTRUCTURE ADAPTING TO CLIMATE CHANGE

21 July 2021

## PRECAST CONCRETE CONSTRUCTION : A GREEN CONSTRUCION

DR. IR. HARI NUGRAHA NURJAMAN, MT.





MINISTRY OF EDUCATION AND CULTURE REPUBLIC OF INDONESIA IPB UNIVERSITY FACULTY OF AGRICULTURAL ENGINEERING AND TECHNOLOGY DEPARTMENT OF CIVIL AND ENVIRONMENTAL ENGINEERING





### DAFTAR ISI

- 01 INTRODUCTION
- 02 PRECAST CONTRUCTION EXAMPLE IN INDONESIA
- 03 RESEARCH OF GREEN CONSTRUCTION
- 04 GREEN BUILDING CODE IN INDONESIA

05 CLOSING








- Sustainable construction is an aspect developed worldwide as a response to climate change
- Use of energy in integrally optimal fashion starting from natural resources, design, construction, operation, and demolition
- Concrete precast system is a method of construction conforming to green construction, since the system applies efficient working method and material such that energy is used optimal


- Integrated design between architects, structure engineer and utility engineer respect to Life Cost Analysis (LCA)
- The building is huge potential for CO2 emission reduction targets, and also the least expensive way to working on it.
- Generally, the concept of sustainable development requires a large initial investment cost, which is often considered to be an additional financial burden for the owner / investor building

#### The Vicious Circle of Blame (adopted from Cadman, 2000)



Property Values and Profitability as Economic Incentives for Sustainable Property Investment by Dipl-Ing Matthias Schaule, Highrise Tower and Tall Building Conference, Munich 2010

Breaking the Vicious Circle of Blame (adopted from RICS, 2008)



Property Values and Profitability as Economic Incentives for Sustainable Property Investment by Dipl-Ing Matthias Schaule, Highrise Tower and Tall Building Conference, Munich 2010






I'm President of Pittsburg, not Paris Man cannot control the climate !

### Are climate change because of human behavior ?

## Introduction

### COVID 19 dan sektor energi





- Penurunan konsumsi energi menyebabkan terjadi penurunan emisi global 5% di Q1 2020 dibandingkan Q1 2019 (8% batubara, 4.5% minyak dan 2.3% gas)
- Penurunan emisi GRK bulan April 2020 mencapai 17% dibandingkan 2019







## 02 – PRECAST CONSTRUCTION EXAMPLE IN INDONESIA





### PRECAST EXAMPLE

Video: High Performance Precast Seismic System The Hive (2014)










PENDAHULUAN

## Video : Prefabricated Prefinished Volumetric Construction di Rumah Sakit Covid Galang (2020)

• Video : Project Tokyo Riverside Apartment 32 Storey With Precast Emulated Cast In Place (2020)

### PRECAST EARTHQUAKE TESTING



Berkeley maximum consider earthquake risk (MCE<sub>R</sub>, T=2500 tahun)



### PRECAST EARTHQUAKE TESTING













e





## 03 - RESEARCH OF GREEN CONSTRUCION





- Performed on research works by Green Building Council of Indonesia (GBCI) (2012-2014)
- inspect how precast construction was elaborated in the determination of green construction category.
- Generally, there exist seven aspects in building assessment, should that building be designed with sustainable concept,

Category	Precast concrete contribute to greenship points
Appropriate Site Development	ASD 6 – Micro climate (Heat island effect – Albedo)
Energy Efficiency and Conservation	EEC P2 – OTTV calculation
Water Conservation	
Material Resources and Cycle	MRC 1 – Building and material reuse MRC 2 – Environmentally processed product MRC 5 – Modular design/prefab material MRC 6 – Regional material
Indoor Health and Comfort	IHC 3 – Chemical pollutant
Building Environment Management	BEM 2 – Pollution of Construcion Activity
Innovation	

- The main green aspect of precast is in Material Resources and Cycle : the concept is known by "3R" : Reduce, Reuse, Recycle
  - Reduce
    - Concrete is local material in Indonesia
    - Design able to save the use of steel bar (as a reward to good quality control)
    - Method save scaffold and zero waste
  - Reuse : precast mold used 10 15 times compare to 2 3 times in conventional system
  - Recycle
    - molding material : iron or fibre
    - Grouting material has a green lable

- Comparing to conventional concrete method :
  - needs a lot of wood formwork and support, and wasted it after construction
  - And also have a lot of wastes : concrete in pouring process and steel in cutting process











Half Slab





Full Slab Precast needs less material for support



Planning of bar bending schedule in the workshop : Close to zero waste in steel bars cutting



Casting in mold at ground floor : Close to zero waste in concrete pouring













High rate of reusing of formwork

- Performed on the use of energy and its environmental impact on several construction systems of low cost apartments in Batam (2011-2012)
- High Performace Earthquake Resistant precast systems with low initial investation in Indonesia (2013-2014)




#### SEMINAR SEKOLAH PASCASARJANA INSTITUT PERTANIAN BOGOR

Nama	ŧ	Hairul Sitepu	
NRP	1	P062059324	
Program Studi	ł.	Pengelolaan Sumberdaya Alam dan Lingkungan	
Bidang Minat		Kebijakan dan Manajemen Lingkungan	
Judul Penelitian	1	Pengembangan Rumah Susun Sederhana Sewa (Rusunawa) Yang Ramah Lingkungan Melalui Optimasi Pelaksanaan Konstruksi Ilijau ( <i>Green</i> <i>Construction</i> )	
Komisi Pembimbing	£	1. Dr. Ir. Aris Munandar	(Ketua)
		2. Prof. Dr. Ir. Bambang Pramu	idya (Anggota)
		3. Dr. Ir. Etty Riani	(Anggota)
		4. Dr. Ir. Rinekso Soekmadi	(Anggota)
Kelompok		Ilmu-Ilmu Sosial	
Hari, Tanggal	i.	09 April 2011	
Pukul	r.	12.00 WIB	
Tempat	1	Ruang Cempaka, Kampus IPB Baranangsiang	

QUANTITATIVE RESEARCH : construction energy and environmental impact

- Energy calculation and environmental impact of each item of construction works based on Goedkoop and Oele
- Equalization process for comparison by the method of LCA (life cycle analysis) through Simapro 5.0
- Starting from the retrieval of natural, manufactured, used, maintenance, to demolition and return to nature

### **CONSTRUCTION MATERIAL OPTIMAZION**



## QUANTITATIVE RESEARCH : construction energy and environmental impact

Selection of construction method alternative

Type and volume of environment friendly materials of each alternative

Life Cycle Analysis of construction materials

Calculation of construction cost of each alternative

Worksheet/ SimaPro

### Life Cycle Assesment (LCA)






Exhibit 1-1. Life Cycle Stages (Source: EPA, 1993)

#### Software SimaPro 5,


Tree diagram : Cement




Tree Diagram : Wood support




Tree Diagran : Steel Bars




### Tree Diagram : Bata Merah (Red Brick)




Tree Diagram : Tile & Saniter



Tree Diagram : Aluminium



#### **RESEARCH LOCATION**



# $\label{eq:QUANTITATIVE RESEARCH: construction energy and environmental impact$



### $\label{eq:QUANTITATIVE RESEARCH: construction energy and environmental impact$

- Conventional :
  - Structural
  - Architectural
- Half Precast :
  - Precast Strucural System
  - Conventional architectural system
- Full precast system both structural and architectural

# $\label{eq:QUANTITATIVE RESEARCH: construction energy and environmental impact$



Half Precast System



construction energy and environmental impact



Full Precast System

## QUANTITATIVE RESEARCH : and environmental impact

#### construction energy



Full Precast System




construction energy and environmental impact


No	Main component	Conventional	Partially	Full Precast
			Precast	
1	Cement	488 ton	499 ton	617 ton
2	Fine aggregate	3.483 m3	3.354 m3	687 m3
3	Coarse aggregatre	339 m3	398 m3	642 m3
4	Reinforcement bar	180 ton	77 ton	122 ton
5	Mold	wood 41 m3	steel 7,9 ton	steel 9,2 ton
6	Perancah	wood 562 m3	steel 7,8 ton	steel 7,8 ton
7	Bata merah	413.216 nos	413.216 nos	-
8	Skill labour	20 org	30 org	40 org
9	Unskill labour	80 org	45 org	15 Org
10	Cost (Rp x 1.000 million)	13,657	11,500	11,434
11	No. of stories /area	4 lt/4.600 m2	4 lt/4.600 m2	4 lt/4.600 m2
12	Construction time (month)	8	6	5

\*) Precast technology used is from one of the national precaster

construction energy and environmental impact




LCA Single Score : Conventional Concrete System



Analyzing 1 plassembly 'PR Semi Precasi': Method: EDIP/UMIP 96 / EDIP World/Dk / single score


LCA Single Score : Half Precast System

## QUANTITATIVE RESEARCH : construction energy and environmental impact



LCA Single Score : Full Precast Concrete System

## QUANTITATIVE RESEARCH : construction energy and environmental impact



Comparison of single score of each alternative. Partially Precast System is 31% lower than conventional system and 6% lower than full precast system

#### construction energy and environmental impact

Construction	Katagori Dampak Lingkungan (Pt)			
alternative dan Pollutant potential of main building material	Chronic toxic waters	Acute toxic waters	Chronic toxic soils	Energy (kWh)
Conventional:				1.253.774,7
-steel bar	5,18 x 10 <sup>8</sup>	4,95 x 10 <sup>7</sup>	2,53 x 10 <sup>7</sup>	
-cement	2,85 x 10 <sup>8</sup>		1,39 x 10 <sup>7</sup>	
-aluminum		3,68 x 10 <sup>6</sup>		
Partially precast:				806.981,9
-cement	2,94 x 10 <sup>8</sup>	2,82 x 10 <sup>7</sup>	1,43 x 10 <sup>7</sup>	
-steel bar	2,27 x 10 <sup>8</sup>	-	1,11 x 10 <sup>7</sup>	
-red brick		9,97 x 10 <sup>6</sup>		
Full precast:				1.008.199,9
-steel bar	4,11 x 10 <sup>8</sup>	3,92 x 10 <sup>7</sup>		
-cement	2,39 x 10 <sup>8</sup>	2,29 x 10 <sup>7</sup>	1,97 x 10 <sup>7</sup>	
-ceramic & sanitary			3,65 x 10 <sup>6</sup>	


Comparison of the environmental impact of major construction material

### ANALYSIS


When evaluated from the construcion energy needs Convensional system 272 kWh/m2, Full precast system 219 kWh/m2, Half precast system yaitu 175 kWh/m2.

Energy needs are considered reasonable for the construction of residential buildings is 240 kWh/m2 that medium-rise apartment construction with precast system can be considered to meet the criteria of green construction.

### ISM (Interpretive structural modelling)




Based on the independence and the driving force (4) Ministry of Public Works and (5) Ministry of Housing as the most relevant sectors (key stakeholders), still has a driving force that is better than (1) the Central Government. Other groups occupy quadrant III (linkage) consists of: (3) Government of Batam, (6) Department of Public Works; (8) business, and (10) as a liaison practitioner.



HANDI CAP

: (1) lack of socialization, (2) limited the quality of human resources; (8) not all contractors understand, (4) lack of oversight, and (11) doubt society, (7) lack of technology; (9) equipment limitations, and (16) failing construction.



Hierarchy Level on the Relation of Element of Main Handicap

: (1) lack of socialization, (2) limited the quality of human resources; (8) not all contractors understand, (4) lack of oversight, and (11) doubt society, (7) lack of technology; (9) equipment limitations, and (16) failing construction. The Concept of Sustainable Low Cost Housing Policy

- LCA and ISM results become the foundation for preparing strategy of sustainable development Low Cost Housing policies.
- The main actors who must play a role is the Ministry of Public Works and the Ministry of Housing.
- Both of these institutions should encourage the development of Low Cost Housing primarily through socialization to enhance capabilities of human resources and understanding of all parties.
- In addition, there should be policies that could encourage the implementation priority for the half precast concrete construction for the successful development of environmentally friendly.









MENTERI PEKERJAAN UMUM DAN PERUMAHAN RAKYAT REPUBLIK INDONESIA

PERATURAN MENTERI PEKERJAAN UMUM DAN PERUMAHAN RAKYAT REPUBLIK INDONESIA NOMOR 21 TAHUN 2021 TENTANG PENILAIAN KINERJA BANGUNAN GEDUNG HIJAU

DENGAN RAHMAT TUHAN YANG MAHA ESA

MENTERI PEKERJAAN UMUM DAN PERUMAHAN RAKYAT REPUBLIK INDONESIA,


- Menimbang : bahwa untuk melaksanakan ketentuan Pasal 123 Peraturan Pemerintah Nomor 16 Tahun 2021 tentang Pelaksanaan Undang-Undang Nomor 28 Tahun 2002 tentang Bangunan Gedung perlu menetapkan Peraturan Menteri Pekerjaan Umum dan Perumahan Rakyat tentang Penilaian Kinerja Bangunan Gedung Hijau;
- Mengingat : 1. Pasal 17 ayat (3) Undang-Undang Dasar Negara Republik Indonesia Tahun 1945;
  - Undang-Undang Nomor 28 Tahun 2002 tentang Bangunan Gedung (Lembaran Negara Republik Indonesia Tahun 2002 Nomor 134, Tambahan Lembaran Negara Republik Indonesia Nomor 4247);
  - Undang-Undang Nomor 39 Tahun 2008 tentang Kementerian Negara (Lembaran Negara Republik Indonesia Tahun 2008 Nomor 166, Tambahan Lembaran Negara Republik Indonesia Nomor 4916);

Mandatory in minimum category for all building construction : in building permit (Persetujuan Bangunan Gedung/PBG)

# Mandatory in several category for goverment building

jdih.pu.go.id

## **KRITERIA BGH**





Peraturan Menteri PUPR Nomor 21 Tahun 2021

KLAS BANGUNAN GEDUNG	DEFINISI	KATEGORI
Klas 1	Bangunan Gedung hunian biasa: Sub-klas 1a: Satu rumah tunggal, satu atau lebih rumah gandeng yang dipisahkan dinding tahan api Sub-klas 1b: Asrama, hostel atau sejenisnya dengan luas paling besar 300 m <sup>2</sup> dan tidak dihuni lebih dari 12 orang	DISARANKAN (RECOMMENDED)
Klas 2	Bangunan Gedung hunian yang terdiri atas 2 atau lebih unit hunian, yang masing-masing merupakan tempat tinggal terpisah	DISARANKAN (RECOMMENDED)
Klas 3 Bangunan Gedung hunian di luar klas 1 dan 2, yang umum digunakan sebagai tempat tinggal lama atau sementara oleh sejumlah orang yang tidak berhubungan		DISARANKAN (RECOMMENDED)
Klas 4Bangunan Gedung hunian yang berada di dalam suatu bangunan ketentuan:- di bawah 3merupakan tempat tinggal yang ada		DISARANKAN (RECOMMENDED)

KR	TER	IA I	<b>BGH</b>


KLAS BANGUNAN GEDUNG	DEFINISI	KATEGORI
lantai; atau - di atas 4 lantai dengan luas kurang dari 50.000 m <sup>2</sup>	dalam bangunan tersebut	
Klas 5 dengan ketentuan: - di bawah 3 lantai; atau - di atas 4 lantai dengan luas kurang dari 50.000 m <sup>2</sup>	Bangunan Gedung yang dipergunakan untuk tujuan usaha profesional, pengurusan administrasi, atau usaha komersial, di luar bangunan klas 6, 7, 8, atau 9	DISARANKAN (RECOMMENDED)
Klas 6 dengan ketentuan: - di bawah 3 lantai; atau - di atas 4 lantai dengan luas kurang dari 5000 m2	Bangunan Gedung toko atau Bangunan Gedung lain yang dipergunakan untuk tempat penjualan barang-barang secara eceran atau pelayanan kebutuhan langsung kepada masyarakat	DISARANKAN (RECOMMENDED)
Klas 7 dengan ketentuan: - di bawah 3 lantai; atau - di atas 4 lantai dengan luas kurang dari 5000 m <sup>2</sup>	Bangunan Gedung yang dipergunakan sebagai penyimpanan -	DISARANKAN (RECOMMENDED)
Klas 8 dengan ketentuan: - di bawah 3 lantai; atau - di atas 4 lantai dengan luas kurang dari 5000 m <sup>2</sup>	Bangunan Gedung laboratorium dan Bangunan Gedung yang dipergunakan untuk tempat pernosesan suatu produksi, perakitan, perubahan, perbaikan, pengepakan, <i>finishing</i> , atau pembersihan barang-barang produksi dalam rangka perdagangan atau penjualan	DISARANKAN (RECOMMENDED)



Peraturan Menteri PUPR Nomor 21 Tahun 2021

KLAS BANGUNAN GEDUNG	DEFINISI	KATEGORI
Klas 9a dengan ketentuan huas sampai dengan 20.000 m <sup>2</sup>	Bangunan Gedung umum untuk pelayanan perawatan kesehatan	DISARANKAN (RECOMMENDED)
Klas 9b dengan ketentuan luas sampai dengan 10.000 m <sup>2</sup>	9b. Bangunan Gedung umum pertemuan yang tidak termasuk setiap bagian dari bangunan yang merupakan klas lain	DISARANKAN (RECOMMENDED)
Klas 10	Sub-klas 10b: Bangunan Gedung bukan hunian berupa sarana atau prasarana yang dibangun terpisah Sub-klas 10a: Struktur berupa sarana atau prasarana yang dibangun terpisah	DISARANKAN (RECOMMENDED)

## PARAMETER PENILAIAN BGH






Peraturan Menteri PUPR Nomor 21 Tahun 2021

- Pengelolaan Tapak 9 Parameter
- Efisiensi Penggunaan Energi 7 Parameter
- Efisiensi Penggunaan Air 3 Parameter
- Kualitas Udara dalam Gedung 3 Parameter
- Material Ramah Lingkungan 2 Parameter
- Pengelolaan Sampah 3 Parameter
- Pengelolaan Air Limbah 2 Parameter


## **VERIFIKASI & VALIDASI**

- Ada parameter yang spesifik
- Ada dukungan referensi
- Ada analisis perhitungan
- Ada implementasi dalam gambar rancangan
- Ada dalam spesifikasi teknis






### **BENTUK VERIFIKASI & VALIDASI**



JIKA MASIH DALAM BENTUK RENCANA TINDAK → DUKUNGAN KOMITMEN BERUPA SURAT PERNYATAAN

### **RANCANGAN BANGUNAN GEDUNG HIJAU**





# 06 – CONCLUSION







## CONCLUSION

Sustainable construction is a topic that emerges in the world construction as a respond to climate change issue.

Precast concrete is a construction system that meets green construction criteria

Precast building in Indonesia started to be applied commonly in government mass rental low-cost housing program (1995).

Qualitative research was conducted on the assessment criteria of Green Building Council of Indonesia (2012-2014) support precast in which the main principle is 3R (reduce, reuse, and recycle).

## CONCLUSION

The quantitative researches were in energy consumption and environmental influence of several construction in Batam (2011-2012), which showed precast system is have less energy consumed and more environmental friendly than conventional system.

High performance earthquake resistant precast concrete structure at low cost (2013-2014) had found specific system configuration based on local available material and technology.

Based on the successfully application, Indonesian government had set the target application of precast concrete about 30% of construction industry until 2019.

## **CONCLUSION**

The result of this research is expected to be a contribution to all construction stakeholder, in order to start to consider optimization of energy consumption and environmental impact in construction and to become part of sustainable earth movement.

Indonesia already have Green Building Code that mandatory for minimum category for general building and several category for government building